

HydraGEN™

HG2 Series HG2R24EU



Technical Data

Diesel Engine Suitability	1 - 8 L
Electrolyte Medium	Potassium Hydroxide
Power Consumption	144 - 180 W
Power Supply	24 VDC
Power Draw	6 - 7.5 A
Environment Temperature (min.)	-40°C -40°F
Environment Temperature (max.)	50°C 122°F

Exterior Details

Housing	Rugged Steel
Re-Filling Requirement	1.5 L Distilled Water 85 hr between refill
Distilled Water Refill Method	Remote fill tank with pump

Convenience

Communication	Cellular
Tracking	GPS
Other	HydraGEN™ App HydraLytics™ Driver notifications

Logistic Data

Dimensions (W x D x H)	686 x 305 x 279 mm 27 x 12 x 11"
Unit Weight	24.1 kg 53.2 lbs
Packaging Dimensions (H x B x T)	432 x 762 x 432 mm 17 x 30 x 17"
Weight Including Packaging	34 kg 75 lbs
Units per Pallet	6
Pallet Type/Size	1220 x 712 mm 48 x 30"
Harmonized Tariff Code	8543 3070

Applications



Delivery Vans



Intercity/City Buses



Refrigerated Trailers



School Buses



Straight Trucks

H₂ZERO